## Canon

## Canon i-SENSYS MF3010 Laser A4 1200 x 600 DPI 18 ppm

Brand : Canon Product family: i-SENSYS Product code: 5252B015

Product name: MF3010

MF3010, Mono Laser, 18ppm A4, Print/Copy/Scan, USB2.0, 8.2kg Canon i-SENSYS MF3010. Print technology: Laser, Printing: Mono printing, Maximum resolution:  $1200 \times 600$  DPI. Copying: Mono copying, Maximum copy resolution:  $600 \times 600$  DPI. Scanning: Colour scanning, Optical scanning resolution:  $600 \times 600$  DPI. Maximum ISO A-series paper size: A4





Printing		Ports & interfaces	
rint technology * Laser rinting * Mono printing  Ouplex printing * *		Standard interfaces USB port USB 2.0 ports quantity	USB 2.0 ✓ 1
Maximum resolution *	1200 x 600 DPI	Network	_
Print speed (black, normal quality, A4/US Letter) *	- 16 ррш	Wi-Fi * Ethernet LAN *	××
Warm-up time Time to first page (black, normal)	10 s 7.8 s	Performance	
Economical printing	<b>√</b>	Card reader integrated	×
DVD/CD printing	×	Internal memory *	64 MB
Copying		Sound pressure level (printing)	65.3 dB
Duplex copying * Copying * Maximum copy resolution * Copy speed (black, normal quality,	Mono copying 600 x 600 DPI	Sound pressure level (copying) Sound pressure level (scanning) Sound power level (standby) Mac compatibility	65.3 dB 65.3 dB 43 dB
A4)	18 cpm	Design	
Time to first copy (black, normal)  Maximum number of copies  Copier resize  N-in-1 copy function (N=)	12 s 9 copies 50 - 200% 2	Market positioning * Built-in display * Display Touchscreen	Home & office ✓ LED
Scanning		Power	
Optical scanning resolution * 60 Maximum scan resolution 96 Maximum scan area A4 Scanner type * Fla	Colour scanning 600 x 600 DPI 9600 x 9600 DPI A4 / Letter (216 x 297) Flatbed scanner	Power consumption (average operating) Power consumption (PowerSave) Power consumption (off) AC input voltage AC input frequency	960 W 450 W 1.4 W 220 - 240 V 50 - 60 Hz
Input colour depth Output colour depth	24 bit 24 bit	System requirements	
Dutput colour depth 24 bit Greyscale levels 256 Gran drivers TWAIN, WIA Film scanning X	Windows operating systems supported Mac operating systems supported Linux operating systems supported	√ √ √	
Fax		Operational conditions	
Duplex faxing Faxing *	×	Operational conditions  Operating relative humidity (H-H)  Operating temperature (T-T)	20 - 80% 10 - 30 °C
Features		Sustainability	•
Maximum duty cycle *	8000 pages per month	Sustainability certificates	ENERGY STAR
Digital sender	X		LINLINGI STAN
Number of print cartridges *	1	Weight & dimensions	
Printing colours *	Black	Weight	8.2 kg

Features		Packaging content	
Page description languages	UFRII-LT	Drivers included	1
Input & output capacity		Bundled software	Presto! Page Manager, MF Toolbox
Total number of input trays *	1	Other features	
Total input capacity *	150 sheets	Dimensions (WxDxH)	372 x 276 x 254 mm
Total output capacity *	100 sheets	Network ready	×
Paper input type	Paper tray	Compatible operating systems	Windows 7/2000/ XP/ Vista Mac OS X Version 10.4.9 - 10.7.x 1 Linux
Paper handling		All-in-one functions	Copy, Print, Scan
Maximum ISO A-series paper size *	A4	Colour all-in-one functions	Scan
Maximum print size	216 x 356 mm	Colour scanning	<b>4</b>
	Card stock, Envelopes, Labels, Plain	Connectivity technology	Wired
Paper tray media types *	paper, Recycled paper, Transparencies	Duplex (double-sided)	×
ISO A-series sizes (A0A9) *	A4, A5		
ISO B-series sizes (B0B9)	B5		
Non-ISO print media sizes	Executive, Index card, Statement		
Envelopes sizes	10, B5, C5, DL		
Custom media width	76 - 216 mm		
Custom media length	127 - 356 mm		

