

## Socomec ITYS 10,000Va/9000W uninterruptible power supply (UPS) Double-conversion (Online) 10 kVA

**Brand :** Socomec

**Product code:** ITY2-TW100B

**Product name :** ITYS 10,000Va/9000W

10000Va/9000W, terminals, 240 V DC, 9 min, 4 A, RS232 - USB - Dry contact, up to 94%

Socomec ITYS 10,000Va/9000W uninterruptible power supply (UPS) Double-conversion (Online) 10 kVA:

### The solution for

- Professional workstations
- Server and corporate networks
- Storage systems
- Industrial automation
- Security systems
- Telecom systems

### Advantages

#### High protection and availability

- True online double conversion technology (VFI) assures high availability and total load protection.
- Constant output voltage and frequency regulation makes ITYS compatible with different applications, operating environments and generator sets.
- Automatic bypass supplies the loads in the event of overloads or faults.

Socomec ITYS 10,000Va/9000W. UPS topology: Double-conversion (Online), Output power capacity: 10 kVA, Output power: 9000 W. AC outlet types: Terminal, Serial interface type: RS-232. Battery voltage: 240 V. Form factor: Tower, Product colour: Grey, Cooling type: Active. Cables included: Input power cable



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery voltage	240 V
Output power capacity *	10 kVA	<b>Design</b>	
Output power *	9000 W	Form factor *	Tower
Waveform *	Sine	Cooling type	Active
Input operation voltage (min) *	176 V	Product colour *	Grey
Input operation voltage (max) *	276 V	Display type	LCD
Input frequency *	45/66 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	208 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Number of input phases	1	<b>Packaging content</b>	
Number of output phases	1	Cables included	Input power cable
Efficiency	92%	Manual	✓
<b>Ports &amp; interfaces</b>		Quick installation guide	✓
AC outlet types	Terminal	<b>Weight &amp; dimensions</b>	
USB port	✗	Width	260 mm
Serial interface	✓	Depth	550 mm
Serial interface type	RS-232	Height	708 mm
RS-232 ports	1	Weight	84 kg
		<b>Logistics data</b>	
		Country of origin	China



8027122549561

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.