



Lenovo ThinkCentre M82 Intel® Pentium G G630 2 DDR3-SDRAM 500 Windows 7 Professional Mini Tower PC

Brand : Lenovo Series : ThinkCentre Model : 3392C7U
Part Number : M82



Lenovo ThinkCentre M82. Processor: 2.7 GHz, Processor: Intel® Pentium G, Processor: G630. Memory: 2 GB, Memory: DDR3-SDRAM. Hard Drive: 500 GB, Optical Drive: DVD-RW. Operating System: Windows 7 Professional. Processor: 64-bit. Processor: 280 MHz. Processor: Mini Tower. Processor: PC. Processor: M82



Processor		Memory	
Processor	Intel	PCI Express	2
Processor	Intel® Pentium G	Memory	
Processor	G630	Processor	Mini Tower
Processor	2	3.5" Drive	1
Processor	2	5.25" Drive	2
Processor	2.7 GHz	Processor	✓
Processor	LGA 1155 (Socket H2)	Processor	Kensington
Processor	3 GB	Processor	PC
Processor	5 GT/s	Processor	
Processor	DMI	Processor	✓
Processor	32 GB	Processor	PC
Processor	64-bit	Processor	
Processor	Intel Pentium G600 Series for Desktop	Processor	64-bit
Processor	Sandy Bridge	Processor	Windows 7 Professional
TDP(Thermal Design Power)	65 W	Processor	
Tcase	69.1 °C	Processor	
PCI Express	2.0	Processor	✗
Processor	1	Processor	✓
Processor	Q0	Processor	✓
Processor	27	Processor	✗
Processor	32 GB	Processor	✗
Processor	DDR3-SDRAM	Processor	✗
Processor	1066 MHz	Processor	✗
Processor	17 GB/s	Processor	✓
Processor		Processor	✓
Processor	2 GB	Processor	✓
Processor	32 GB	Processor	✗
Processor	DDR3-SDRAM	Processor	✗
Processor	1 x 2 GB	Processor	✓
Processor	4x DIMM	Processor	✓
Processor	PC	Processor	✓

PC Specs		Server Specs	
Processor *	500 MHz	Processor	✓
Memory *	DVD-RW	Memory	✓
Storage	1	Storage	✓
Power Supply	500 MHz	Power Supply	37.5 x 37.5 mm
Network Interface	SATA III	Network Interface	SR05S
OS	7200 mm	CPU (mm)	1
OS	✓	VT-d(Virtualization Technology for Directed I/O)	✗
OS		VT-x(Virtualization Technology)	✓
OS	✓	OS	✓
OS	OS	OS	53483
OS	OS	OS	✗
OS	OS	OS	✗
OS	OS	OS	✗
OS	OS	OS	✗
OS	OS	OS	✗
OS		OS	280 mm
OS	✓	OS	10 - 35 mm
OS	10,100,1000 mm/mm	OS	-40 - 60 mm
OS	10/100/1000Base-T(X)	OS	20 - 80 mm
WLAN	✗	OS	20 - 90 mm
OS	✗	OS	RoHS
OS & OS		OS	175 mm
USB 2.0	4	OS	412 mm
USB 3.2 Gen 1 (3.1 Gen 1) A	4	OS	365 mm
VGA(D-Sub)	1	OS	11 mm
DVI	✗	OS	✓
OS	1	OS	✓
OS (RJ-45)	1	OS	✗
OS, OS	✓	OS	1 x 3.5", 2 x 5.25"
OS	1	OS	2 x 3.5"
DC	✓	OS	Gigabit Ethernet
OS	1	OS	Intel
OS		OS	OS
PCI	1	OS	OS, OS
PCI	1	OS	OS

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.