



Canon EOS 1300D + 18-55mm IS SLR Camera Kit 18 MP CMOS 5184 x 3456 pixels Black

Brand : Canon

Product family: EOS

Article code: 1160C121

Product name : 1300D + 18-55mm IS

EOS 1300D + 18-55mm IS, 18MP, CMOS, TTL-CT-SIR, 3:2, DIGIC 4+, WLAN, NFC, SD/SDHC/SDXC, HDMI, USB

Canon EOS 1300D + 18-55mm IS SLR Camera Kit 18 MP CMOS 5184 x 3456 pixels Black:

Take distinctive photos that set you apart

Capture superb detailed images thanks to a large 18.0 Megapixel APS-C size sensor
Print your images up to A2 size or creatively crop them and still achieve great quality.

Natural low light shots

Take memorable, atmospheric pictures in low light with a large ISO sensitivity range of ISO 100-6400 (expandable to ISO 12,800), which reduces the need for flash – so you can capture the natural ambience of every precious moment.

Beautiful background blur

Create stunning portrait shots that emphasise your subject against beautiful soft blurred backgrounds thanks to the shallow depth of field associated with DSLR photography.

Superb detail and colour

Shoot superb images with the details, colours and contrast exactly as you remember thanks to the DIGIC 4+ processor.



Picture quality		Display	
Camera type *	SLR Camera Kit	Flip-out screen	✗
Megapixel *	18 MP	Vari-angle LCD display	✗
Sensor type *	CMOS	Field of view	100%
Maximum image resolution *	5184 x 3456 pixels	Viewfinder	
Still image resolution(s) *	3:2: (L) 5184 x 3456, (M) 3456 x 2304, (S1) 2592 x 1728, (S2) 1920 x 1280, (S3) 720 x 480 4:3: (L) 4608 x 3456, (M) 3072 x 2304, (S1) 2304 x 1728, (S2) 1696 x 1280, (S3) 640 x 480 16:9: (L) 5184 x 2912, (M) 3456 x 1944, (S1) 2592 x 1456, (S2) 1920 x 1080, (S3) 720 x 400 1:1: (L) 3456 x 3456, (M) 2304 x 2304, (S1) 1728 x 1728, (S2) 1280 x 1280, (S3) 480 x 480	Magnification	0.8x
		Ports & interfaces	
		PictBridge *	✓
		USB version *	2.0
		HDMI *	✓
	HDMI connector type	Mini	
	USB port	✓	
Image stabilizer *	✓	Network	
Image stabilizer location	Lens	Wi-Fi *	✓
Supported aspect ratios	3:2	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Total megapixels	18.7 MP	Near Field Communication (NFC) *	✓
Image sensor size (W x H)	0.878 x 0.587" (22.3 x 14.9 mm)	Camera	
Sensor format	Advanced Photo System type-C (APS-C)	White balance *	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Shade, Tungsten
Image formats supported *	JPS, RAW	Scene modes *	Close-up (macro), Food, Night portrait, Portrait, Sports, Landscape
Lens system		Shooting modes *	Auto, Movie, Scene
Focal length range	18 - 55 mm	Photo effects *	Neutral
Lens mount interface	Canon EF, Canon EF-S	Self-timer delay *	2,10 s
Focusing		Brightness adjustment	✓
Focus *	TTL-CT-SIR		
Focus adjustment *	Auto/Manual		

Focusing		Camera	
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Servo Auto Focus	Camera playback	Movie, Single image, Slide show, Thumbnails
Auto Focus (AF) points	9	Diopter correction	✓
Auto Focus (AF) lock	✓	Diopter adjustment (D-D)	-2.5 - 0.5
Auto Focus (AF) assist beam	✓	Playback zoom (max)	10x
Exposure		Languages support	Multi
ISO sensitivity (min) *	100	Histogram	✓
ISO sensitivity (max) *	6400	Live view	✓
ISO sensitivity	100, 200, 400, 800, 1600, 3200, 6400, Auto	GPS (satellite)	✗
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Camera file system	DCF 2.0, DPOF, Exif 2.3, RAW
Light exposure control	Program AE	Eye relief	0.827" (2.1 cm)
Light exposure correction *	± 5EV (1/2EV; 1/3EV step)	Playback modes	Zoom
Light metering *	Centre-weighted, Partial	Built-in processor	✓
Auto Exposure (AE) lock	✓	Image processor	DIGIC 4+
Shutter		Windows operating systems supported	✓
Fastest camera shutter speed *	1/4000 s	Mac operating systems supported	✓
Slowest camera shutter speed *	30 s	Design	
Camera shutter type	Electronic	Product color *	Black
Flash		Material	Carbon fiber, Fiberglass, Polycarbonate
Flash modes *	Auto, Flash off, Flash on, Red-eye reduction, Second curtain synchro	Battery	
Flash guide number	362.2" (9.2 m)	Battery technology *	Lithium-Ion (Li-Ion)
Flash recharging time	2 s	Battery life (CIPA standard)	500 shots
Flash sync-speed	1/200 s	Battery type	LP-E10
Flash exposure compensation	✓	Number of batteries supported	1
Flash exposure correction	±2EV (1/2, 1/3 EV step)	Battery level indicator	✓
Shoe mounting point	✓	Operational conditions	
Video		Operating temperature (T-T)	0 - 40 °C
Video recording *	✓	Operating relative humidity (H-H)	0 - 85%
Maximum video resolution *	1920 x 1080 pixels	Weight & dimensions	
HD type *	Full HD	Width	5.08" (129 mm)
Video resolutions	640 x 480, 1280 x 720, 1920 x 1080 640x480@25fps, 640x480@30fps, 1280x720@50fps, 1280x720@60fps, 1920x1080@24fps, 1920x1080@25fps, 1920x1080@30fps	Depth	3.06" (77.6 mm)
Resolution at capture speed		Height	3.99" (101.3 mm)
Analog signal format system	NTSC, PAL	Weight (including battery)	17.1 oz (485 g)
Video formats supported	H.264, MOV	Packaging content	
Audio		Hand strap	✓
Built-in microphone *	✓	Battery charger included	✓
Audio formats supported	LPCM	Batteries included	✓
Memory		Carrying case	✓
Compatible memory cards *	SD, SDHC, SDXC	Quick start guide	✓
Memory slots	1	Bundled software	Digital Photo Professional 4.4.0
Display		Other features	
Display *	LCD	Power source type	Battery
Touchscreen *	✗		
Display diagonal *	3"		
Display resolution (numeric)	920000 pixels		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.