Canon EOS 77D EF-S 10-18 mm f 4.5 5.6 IS STM SLR Camera Body 24.2 MP CMOS 6000 x 4000 pixels Black

Brand : Canon

Product family: EOS

Article code: 1892C081

Product name : 77D EF-S 10-18 mm f 4.5 5.6 IS STM

EOS 77D, EF-S 10-18 mm f 4.5 5.6 IS STM, RODE Microphone, 64Gb SD Card

Canon EOS 77D EF-S 10-18 mm f 4.5 5.6 IS STM. Camera type: SLR Camera Body, Megapixel: 24.2 MP, Sensor type: CMOS, Maximum image resolution: 6000 x 4000 pixels. ISO sensitivity (max): 25600. Focal length range: 10 - 18 mm. Wi-Fi. HD type: Full HD, Maximum video resolution: 1920 x 1080 pixels. Display diagonal: 3", Touchscreen. Viewfinder type: Optical. PictBridge. Weight: 19 oz (540 g). Product color: Black





Picture quality

Picture quality		Display	
			2.2
Camera type *	SLR Camera Body	Display aspect ratio	3:2
Megapixel * Sensor type *	24.2 MP CMOS	Flip-out screen	✓
Maximum image resolution *	6000 x 4000 pixels	Vari-angle LCD display	
Still image resolution(s) *	6000 x 4000, 3984 x 2656, 2976 x 1984, 1920 x 1280, 5328 x 4000, 3552 x 2664, 2656 x 1992, 1696 x 1280, 6000 x 3368, 3984 x 2240, 2976 x 1680, 1920 x 1080, 4000 x 4000, 2656 x 2656, 1984 x 1984,	Field of view	100%
		Second display	×
		Viewfinder	
		Viewfinder type	Optical
		Magnification	0.82x
Supported aspect ratios	1280 x 1280 1:1, 3:2, 4:3, 16:9	Ports & interfaces	
Total megapixels	25.8 MP	PictBridge *	٠
Image sensor size (W x H)	0.878 x 0.587" (22.3 x 14.9 mm)	USB version *	2.0
	Advanced Photo System type-C	HDMI *	<u> </u>
Sensor format	(APS-C)	HDMI connector type	- Mini
Image formats supported *	JPG, RAW	Microphone in	 ✓
Lens system			
Focal length range	10 - 18 mm	Network	
Lens mount interface	Canon EF, Canon EF-S	Bluetooth *	✓
Focusing		Bluetooth version	4.1
Focus *	TTL-CT-SIR	Bluetooth Low Energy (BLE)	 Image: A set of the set of the
Focus adjustment *	Auto	Wi-Fi *	J
	Al Focus, Centre weighted Auto	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Auto focusing (AF) modes *	Focus, One Shot Focus, Servo Auto	Near Field Communication (NFC) *	
	Focus		 Image: A start of the start of
Closest focusing distance	Focus	Camera	•
Closest focusing distance	9.84" (0.25 m)	Camera	Auto, Cloudy, Custom modes,
Auto Focus (AF) points	9.84" (0.25 m) 49	. ,	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten
Auto Focus (AF) points Auto Focus (AF) points selection	9.84" (0.25 m)	Camera White balance *	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten Candlelight, Children, Close-up
Auto Focus (AF) points Auto Focus (AF) points selection Auto Focus (AF) lock	9.84" (0.25 m) 49 Auto	Camera	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten
Auto Focus (AF) points Auto Focus (AF) points selection	9.84" (0.25 m) 49 Auto	Camera White balance *	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten Candlelight, Children, Close-up (macro), Food, Landscape, Night
Auto Focus (AF) points Auto Focus (AF) points selection Auto Focus (AF) lock Auto Focus (AF) assist beam	9.84" (0.25 m) 49 Auto	Camera White balance * Scene modes *	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten Candlelight, Children, Close-up (macro), Food, Landscape, Night portrait, Portrait Aperture priority, Auto, Manual,
Auto Focus (AF) points Auto Focus (AF) points selection Auto Focus (AF) lock Auto Focus (AF) assist beam Exposure	9.84" (0.25 m) 49 Auto ✓	Camera White balance * Scene modes * Shooting modes *	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten Candlelight, Children, Close-up (macro), Food, Landscape, Night portrait, Portrait Aperture priority, Auto, Manual, Scene, Shutter priority
Auto Focus (AF) points Auto Focus (AF) points selection Auto Focus (AF) lock Auto Focus (AF) assist beam Exposure ISO sensitivity (min) *	9.84" (0.25 m) 49 Auto ✓ ✓	Camera White balance * Scene modes * Shooting modes * Photo effects *	Auto, Cloudy, Custom modes, Daylight, Shade, Tungsten Candlelight, Children, Close-up (macro), Food, Landscape, Night portrait, Portrait Aperture priority, Auto, Manual, Scene, Shutter priority Black&White

Expective		Comoro	
Exposure		Camera	
Light exposure modes *	Auto, Manual	Diopter adjustment (D-D)	-3 - 1
Light exposure control	Program AE	Playback zoom (max)	10x Multi
Light exposure correction *	± 5EV (1/2EV; 1/3EV step) Centre-weighted, Evaluative (Multi-	Languages support Live view	
Light metering *	pattern), Partial, Spot		
Auto Exposure (AE) lock	1	Orientation sensor	
Shutter		Camera file system	DPOF 1.1, Exif 2.3
	1/4000 c	Eye relief	0.748" (1.9 cm)
Fastest camera shutter speed * Slowest camera shutter speed *	1/4000 s 30 s	Built-in processor	V DIGIC 7
Camera shutter type	Electronic	Image processor	Windows 10 Education, Windows 10
	Licetonie		Education x64, Windows 10
Flash			Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows
Flash modes *	Auto, Manual, Red-eye reduction		10 Home x64, Windows 10 Home, Windows
Flash guide number	472.4" (12 m)		Core, Windows 10 Pro, Windows 10
Flash recharging time	3 s		Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows
External flash connector	1/200	Windows operating systems	7 Home Basic, Windows 7 Home
Flash sync-speed	1/200 s	supported	Basic x64, Windows 7 Home Premium, Windows 7 Home
Flash exposure compensation			Premium x64, Windows 7
Flash exposure correction	±2EV (1/2, 1/3 EV step)		Professional, Windows 7
Shoe mounting point	×		Professional x64, Windows 7 Starter, Windows 7 Starter x64,
Shoe mounting point type	Hot shoe		Windows 7 Ultimate, Windows 7
Video			Ultimate x64, Windows 8, Windows 8.1
Video recording *	 Image: A set of the set of the		Mac OS X 10.10 Yosemite, Mac OS X
Maximum video resolution *	1920 x 1080 pixels	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12
HD type *	Full HD		Sierra, Mac OS X 10.9 Mavericks
Video resolutions	640 x 480,1280 x 720,1920 x 1080	Design	
Motion JPEG frame rate	50 fps	Product color *	Black
Resolution at capture speed	640x480@25fps, 1280x720@25fps, 1280x720@50fps,	Battery	
	1920x1080@25fps	Battery technology *	Lithium-Ion (Li-Ion)
Analog signal format system	NTSC, PAL	Number of batteries supported	1
Video formats supported	MP4	Battery level indicator	1
Audio		Operational conditions	
Built-in microphone *	1		0 - 40 °C
Audio formats supported	AAC, LPCM	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 0 - 85%
Memory			0 - 05 /0
Compatible memory cards *		Weight & dimensions	
Memory slots	SD, SDHC, SDXC 1	Width	5.16" (131 mm)
-	±	Depth	3" (76.2 mm)
Display		Height Weight	3.93" (99.9 mm) 19 oz (540 g)
Display *	TFT	Lens diameter	19 02 (540 g) 2.62" (6.65 cm)
Touchscreen *	 Image: A set of the set of the	Lens length	2.43" (6.18 cm)
Display diagonal *	3"	Lens weight	7.58 oz (215 g)
Display diagonal (metric)	3.03" (7.7 cm)	Packaging content	
Display resolution (numeric)	1040000 pixels		
		Hand strap	
		Battery charger included	1
		Batteries included	 Image: A second s
		Quick start guide	 Image: A set of the set of the
			Digital Photo Professional 4 EOS

Bundled software

Digital Photo Professional 4 EOS Utility EOS Lens Registration Too EOS Web Service Registration Tool EOS Sample Music Picture Style Editor **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.